



Marine Generator Set Specifications

Model	kW	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in.) Housed / Unhoused	Weight kg (lb)
40EOZD	40.0	60	4	1800	1	120/240	150.0*	1743 (68.62) x 767 (30.20) x 1035 (40.75) 1625 (63.96) x 767 (30.20) x 956 (37.63)	994 (2192) 917 (2022)
					3	120/208	139.0		
					3	120/240	120.0		
					3	127/220	131.0		
					3	139/240	120.0		
33EFOZD	33.0	50	4	1500	3	277/480	60.0	1743 (68.62) x 767 (30.20) x 1035 (40.75) 1625 (63.96) x 767 (30.20) x 956 (37.63)	994 (2192) 917 (2022)
					1	110/220	136.0*		
					3	110/190	125.0		
					3	110/220	108.0		
					3	220/380	63.0		
55EOZD	55.0	60	4	1800	3	230/400	60.0	1870 (73.62) x 767 (30.20) x 1035 (40.75) 1737 (68.39) x 767 (30.20) x 956 (37.63)	1202 (2650) 1125 (2480)
					1	120/240	221.0*		
					3	120/208	191.0		
					3	120/240	165.0		
					3	127/220	180.0		
40EFOZD	40.0	50	4	1500	3	139/240	165.0	1870 (73.62) x 767 (30.20) x 1035 (40.75) 1737 (68.39) x 767 (30.20) x 956 (37.63)	1202 (2650) 1125 (2480)
					3	277/480	83.0		
					1	110/220	182.0		
					3	110/190	152.0		
					3	110/220	131.0		
65EOZD	65.0	60	4	1800	3	220/380	76.0	1870 (73.62) x 767 (30.20) x 1035 (40.75) 1737 (68.39) x 767 (30.20) x 956 (37.63)	1202 (2650) 1125 (2480)
					1	120/240	221.0*		
					3	120/208	226.0		
					3	120/240	195.0		
					3	127/220	213.0		
50EFOZD	50.0	50	4	1500	3	139/240	195.0	1870 (73.62) x 767 (30.20) x 1035 (40.75) 1737 (68.39) x 767 (30.20) x 956 (37.63)	1202 (2650) 1125 (2480)
					3	277/480	98.0		
					1	110/220	205.0*		
					3	110/190	190.0		
					3	110/220	164.0		
80EOZD	80.0	60	6	1800	3	230/400	90.0	2127 (83.73) x 811 (31.91) x 1035 (40.75) 2004 (78.90) x 811 (31.91) x 956 (37.63)	1372 (3025) 1295 (2855)
					1	120/240	241.0		
					3	127/220	262.0		
					3	139/240	241.0		
					3	277/480	120.0		
70EFOZD	70.0	50	6	1500	3	240/416	122.0	2127 (83.73) x 811 (31.91) x 1035 (40.75) 2004 (78.90) x 811 (31.91) x 956 (37.63)	1372 (3025) 1295 (2855)
					3	110/190	266.0		
					3	110/220	230.0		
					3	220/380	133.0		
					3	230/400	126.0		
99EOZD	99.0	60	6	1800	3	240/416	139.0	2251 (89.00) x 811 (31.91) x 1035 (40.75) 2138 (84.15) x 811 (31.91) x 956 (37.63)	1497 (3300) 1420 (3130)
					3	120/208	298.0		
					3	120/240	298.0		
					3	127/220	325.0		
					3	139/240	298.0		
80EFOZD	80.0	50	6	1500	3	277/480	149.0	2251 (89.00) x 811 (31.91) x 1035 (40.75) 2138 (84.15) x 811 (31.91) x 956 (37.63)	1497 (3300) 1420 (3130)
					3	110/190	304.0		
					3	110/220	263.0		
					3	220/380	152.0		
					3	230/400	145.0		
125EOZD	125.0	60	6	1800	3	240/416	173.0	2450 (96.46) x 811 (31.91) x 1128 (44.39) 2291 (90.20) x 811 (31.91) x 1057 (41.63)	1762 (3885) 1683 (3710)
					3	120/208	417.0		
					3	120/240	361.0		
					3	127/220	410.0		
					3	139/240	376.0		
100EFOZD	100.0	50	6	1500	3	277/480	188.0	2450 (96.46) x 811 (31.91) x 1128 (44.39) 2291 (90.20) x 811 (31.91) x 1057 (41.63)	1762 (3885) 1683 (3710)
					3	110/190	380.0		
					3	110/220	328.0		
					3	220/380	190.0		
					3	230/400	180.0		
150EOZD	150.0	60	6	1800	3	240/416	217.0	2506 (98.66) x 811 (31.91) x 1128 (44.39) 2347 (92.41) x 811 (31.91) x 1057 (41.63)	1854 (4089) 1775 (3913)
					3	120/208	521.0		
					3	120/240	451.0		
					3	127/220	492.0		
					3	139/240	451.0		
125EFOZD	125.0	50	6	1500	3	277/480	226.0	2506 (98.66) x 811 (31.91) x 1128 (44.39) 2347 (92.41) x 811 (31.91) x 1057 (41.63)	1854 (4089) 1775 (3913)
					3	110/190	475.0		
					3	110/220	410.0		
					3	220/380	237.0		
					3	230/400	226.0		
180EOZD	180.0	60	6	1800	3	240/416	260.0	2506 (98.66) x 960 (37.80) x 1192 (46.91) 2365 (93.12) x 960 (37.80) x 1121 (44.15)	2011 (4433) 1931 (4258)
					3	120/208	625.0		
					3	120/240	541.0		
					3	127/220	590.0		
					3	139/240	542.0		
150EFOZD	150.0	50	6	1500	3	277/480	271.0	2506 (98.66) x 960 (37.80) x 1192 (46.91) 2365 (93.12) x 960 (37.80) x 1121 (44.15)	2011 (4433) 1931 (4258)
					3	110/190	570.0		
					3	110/220	492.0		
					3	220/380	285.0		
					3	230/400	271.0		

* Amps based on derated kW at this voltage connection. Consult the specification sheet for kW rating.